Wessell, Nickel & Gross

Grand Piano Damper Action Order Form

<u>Contact Information</u>	
Date	Country
Name	Zip / Postal
Address	Phone
City	Email
State/Province	
Make & Model of Piano	Serial Number of Piano
Damper Action (Back Action)	
Please note that custom parts are non-refundable	
Rails drilled and assembled	
□ Yes □ No Total no. of dampers	-
Flange Rail	
 Thin (Requires 72mm from belly rail to center of damper wire) Thick (Requires 86mm from belly rail to center of damper wire) 	
Under Levers	
Spoon Length	
☐ Short (Under lever center to spoon length of 73.6mm)	
□ Medium (Under lever center to spoon length of 76.6mm)	
□ Long (Under lever center to spoon length of 81.6mm)	
Sostenuto Tab	
□ WNG Standard Top Flange (low sostenuto tab height)	
□ WNG Aftermarket Top Flange (high sostenuto tab height)	
Leading (additional charge of \$50.00 for custom leading)	
☐ Standard Leading (2 Leads [32], 1 Outside Lead [12], 1 Inside Lead [12], 0 Leads [12]) ☐ Custom Leading (2 Leads, 1 Outside Lead, 1 Inside Lead, 0 Leads)	
Damper Assist Springs (35 springs per kit)	
No. of Damper Assist Spring Kits (35 springs per kit, \$18.00 per kit)	
No. of notes to install with springs (installation charge of \$1 per note)	
Damper Heads & Wires (additional charge)	
□ Yes □ No	
□ Ebony Satin □ Ebony Polish	
No. of bass dampers	
Sostanuta Pad Vit (additional abance of \$55.00)	
Sostenuto Rod Kit (additional charge of \$75.00) □ Include Sostenuto Rod Kit	
☐ Assemble to customer specifications (additional charge of \$20.00 and scale stick required)	
Tassemble to customer specifications (additional charge of φ20.00 and scale stick required)	
<u>Comments / Special Requirements</u>	
Section for WNG Use Only	
A B C	S/O#